Certificate No:

DNV.GL

MEDB000057F

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

This is to certify:

That the Primary deck coverings

with type designation(s) SikaFloor® Marine 120

Issued to Sika Services AG Zürich, ZH, Switzerland

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2018/773, item No. MED/3.1. SOLAS 74 as amended, Regulation II-2/4, II-2/6 & X/3, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2024-07-07**. Issued at **Høvik** on **2019-07-08**

DNV GL local station: Augsburg

Approval Engineer: Nanna Martine Jacobsen




Notified Body No.: **0575** for DNV GL AS

Roald Vårheim Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005. The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written

NORWEGIAN ACCREDITATION





Page 1 of 2

Job Id: **344.1-004305-7** Certificate No: **MEDB000057F**

Product description "SikaFloor® Marine 120"

Primary deck covering system composed of Cement binders and Mineral aggregates.

Maximum thickness is 30 mm. Density: 900 Kg/m³. Maximum gross calorific value: 42.1 MJ/m² (1.3 MJ/kg).

Application/Limitation

Primary deck covering, not generating excessive quantities of smoke nor toxic products in a fire.

The product may also be used as floor covering in accordance with IMO 2010 FTP code part 5 appendix 4 paragraph 4.9.2.

Approved colour (tested colour): Grey and brighter colours. Maximum organic content: 8.49 wt%

Not to be used as an integrated part of horizontal class A division, unless tested as such.

Each product is to be supplied with its manual for installation and use.

Type Examination documentation

Test report No. 241.4IM0090/10 dated 15 March 2010 from LAPI, Prato, Italy. Test report No. 241.4IM0100/10 dated 15 March 2010 from LAPI, Prato, Italy.

Tests carried out

Tested according to IMO 2010 FTP Code part 5 and Annex 2 item 2.2 and 2.3.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, firetechnical rating, the MED Mark of Conformity and USCG approval number if applicable (see first page).