$\mathsf{DNV} \cdot \mathsf{GL}$

Certificate No: MEDB00001VF

EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of the Kingdom of Norway.

This is to certify:

That the Primary deck coverings

with type designation(s) Sikafloor® Marine-530

Issued to

Sika Services AG ZURICH, Switzerland

is found to comply with the requirements in the following Regulations/Standards: Regulation (EU) 2015/559,

Annex A.1, item No. A.1/3.1 and Annex B, Module B in the Directive; SOLAS 74 as amended, Regulation II-2/4, II-2/6 & X/3, 2000 HSC Code 7 and IMO 2010 FTP Code

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until 2021-12-05.

Issued at Høvik on 2016-12-06

DNV GL local station:

Augsburg

Approval Engineer:

Tomasz Werchowicz


Notified Body


No.: **0575**

for **DNV GL AS**

Vidar Dolonen Head of Notified Body

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005.







Form code: MED 201.NOR Revision: 2016-08 $\ensuremath{\mathbb{C}}$ DNV GL 2014. DNV GL and the Horizon Graphic are trademarks of DNV GL AS.

Job Id: **344.1-006168-1** Certificate No: **MEDB00001VF**

Product description

"Sikafloor® Marine-530"

is a two component self-levelling product based on polyurethane resins.

Max thickness: 2 mm Nominal density: 1.4 g/cm³

Mixing ratio: 15.8 kg of "A" component (colored liquid) to 4.2 kg of "B" component (brownish

transparent liquid)

Application/Limitation

Primary deck covering, not generating excessive quantities of smoke nor toxic products in fire.

The product may also be used as floor covering.

Not to be used as an integrated part of horizontal class A division unless tested as such.

Each product is to be supplied with its manual for installation and maintenance.

Type Examination documentation

Test Reports:

- 20661929-40, APS4-Mü/Wa dated 22nd June 2016,
- 20661929-50, APS4-Mü/Wa dated 22nd June 2016,

both from DMT-Test Laboratory for Fire Protection, Dortmund, Germany.

Tests carried out

Tested according to IMO 2010 FTP Code part 2 and 5.

Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation, fire technical rating, Mark of Conformity and USCG approval number (see first page).

Form code: MED 201.NOR Revision: 2016-08 www.dnvgl.com Page 2 of 2