

Desso Textile floor covering - Broadloom


Tide

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424	Tufted 1/10 "						
Aspect	ISO 2424	Structured loop pile (pattern repeat: L 54cm / W 18cm)						
Dye method	Solution dyed							
Width	cm	400	ft	13.1				
Primary backing	ISO 2424	Polyester - polyamide fleece						
Secondary backing	ISO 2424	Polypropylene woven - Sandwich Backing						
Pile fibre composition	ISO 2424	BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **						
Total thickness	ISO 1765	mm	8.0	inch	0.3			
Effective pile thickness	ISO 1766	mm	4.8	inch	0.19			
Total mass	ISO 8543	g/m ²	2250	oz/yd ²	66.4			
Total pile mass	ISO 2424	g/m ²	710	oz/yd ²	21.0			
Effective pile mass	ISO 8543	g/m ²	440	oz/yd ²	13.0			
Pile density	ISO 8543	g/cm ³	0.092	lb/in ³	0.0033			
Number of tufts	ISO 1763	/dm ²	1580	/yd ²	132104			
Stroll test	ISO 6356	kV	≤ 2,0					
Vertical resistance	ISO 10965	Ohm						
Horizontal resistance	ISO 10965	Ohm						
Use classification	EN 1307	32 Commercial - general use						
Luxury rating	EN 1307	LC 2						
Impact sound reduction ΔL _w	ISO 10140	dB	30					
Sound absorption	ISO 354	Freq. Hz	125	250	500	1000	2000	4000
		α _s	0.00	0.06	0.13	0.30	0.52	0.51
Noise reduction	ISO 354	α _w	0.25					
Thermal resistance	ISO 8302	m ² .K/W	≤ 0,17					
Flammability	EN 13501-1	Cfl - s1 (glued tested)						
Prodis - GUT	www.pro-dis.info	36D3F3BA						

CE EN 14041 0493-CPR-0003

Manufactured by:
Tarkett BV
Parallelweg 14
NL - 5051 HG Goirle



Product is also certified for:
Certificate of Fire Approval IMO Res. MSC.
307 (88) - (FTP Code), Annex 1, Part 2.
Suitable for restricted areas only (cabins and
corridors), not suitable for escape routes.



ECONYL®
Made with 100% Regenerated Nylon



Quality- and Environmental
Management System Certification
ISO 9001 & ISO 14001



Tarkett's flooring products are to be installed in full accordance with DESSO installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Tarkett's flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to amend this specification without giving prior notice. For the latest versions of the technical specifications, visit www.desso.com

EN-20180308



THE ULTIMATE
FLOORING EXPERIENCE

A Tarkett Company